



BUILDING BLOCKS C 2.0


Concrete / Compression
Construction / Component
Cement




Concrete




Compression



Construction



Component




Cement




Milliken®


Building Blocks C 2.0 Pattern




Concrete
CON79-174 DIM GREY



Compression
CPR79-174 DIM GREY



Cement
CEM79-174 DIM GREY



Construction
COS79-174 DIM GREY



Component
CPN79-174 DIM GREY



Concrete in Dim Grey, monolithic installation



Compression in Dim Grey, monolithic installation



Construction in Dim Grey, monolithic installation



Construction in Pistachio Grey, monolithic installation



Component in Pistachio Grey (left), Construction in Ash Grey(right), monolithic installation, Backstitch in Loop(middle), ashlar installation



Component in Zest Yellow, monolithic installation



Concrete in Flint Grey and Zest Yellow, monolithic installation



Construction in Slate Grey and Electric Blue, monolithic installation



Construction, Concrete and Compression in Ash Grey, monolithic installation



Concrete and Compression in Slate Grey, monolithic installation



Cement in Coal Grey, Point 3 in Giant Sequoia with Lava, monolithic installation



Compression in Coal Grey, Point 3 in Betula with Plywood, monolithic installation

COLORLINE

Concrete



CON13-180 ASH GREY



CON154-180 ANCHOR GREY



CON118-174 FLINT GREY



CON79-174 DIM GREY



CON118-106 SLATE GREY



CON141-180 PISTACHIO GREY



CON118-231 ZEST YELLOW



CON123-19 ELECTRIC BLUE




CON119-154 COAL GREY

Compression



CPR13-180 ASH GREY



CPR154-180 ANCHOR GREY



CPR118-174 FLINT GREY



CPR79-174 DIM GREY



CPR118-106 SLATE GREY



CPR141-180 PISTACHIO GREY



CPR118-231 ZEST YELLOW




CPR123-19 ELECTRIC BLUE




CPR119-154 COAL GREY

Construction



COS13-180 ASH GREY



COS154-180 ANCHOR GREY



COS118-174 FLINT GREY



COS79-174 DIM GREY



COS118-106 SLATE GREY



COS141-180 PISTACHIO GREY



COS118-231 ZEST YELLOW




COS123-19 ELECTRIC BLUE



COS119-154 COAL GREY

Component



CPN13-180 ASH GREY



CPN154-180 ANCHOR GREY



CPN118-174 FLINT GREY



CPN79-174 DIM GREY



CPN118-106 SLATE GREY




CPN141-180 PISTACHIO GREY



CPN118-231 ZEST YELLOW



CPN123-19 ELECTRIC BLUE



CPN119-154 COAL GREY

Cement



CEM13-180 ASH GREY



CEM154-180 ANCHOR GREY



CEM118-174 FLINT GREY



CEM79-174 DIM GREY



CEM118-106 SLATE GREY



CEM141-180 PISTACHIO GREY



CEM118-231 ZEST YELLOW



CEM123-19 ELECTRIC BLUE



CEM119-154 COAL GREY



BUILDING BLOCKS C 2.0

Concrete / Compression / Construction
Component / Cement

SPECIFICATION

Construction - Tufted, Textured Loop

Tile Size - 50cm X 50cm (19.7" X 19.7")

Face Fiber - 100% Milliken Certified Nylon

Dye Method - Solution Dyed

Standard Backing - PVC-Free WellBAC™ Function

Available with TractionBack®

Nominal Total Thickness - 5.3 mm AVG.

5.5 mm AVG. (Construction)

Flammability - ≥ 0.45 (Class I)

Texture Appearance Retention Rating (TARR) - Heavy

Indoor Air Quality - CRI Green Label Plus™

GLP3200, Carpet Category 14X

技术指标

结构 - 簇绒织造圈绒结构

产品尺寸 - 50厘米 X 50厘米 (19.7 X 19.7英寸)

表层纤维 - 100% 美利肯认证尼龙

染色技术 - 原液染色

标准底垫 - 不含PVC之 WellBAC™ Function弹性底背

可选装TractionBack® 免胶

额定总厚度 - 5.3 毫米 平均

5.5 毫米 平均 (Construction)

阻燃性 - ≥ 0.45 (一级)

外观保持等级 (TARR) - 频繁商业使用

室内空气质量 CRI Green Label Plus™ - GLP3200, 地毯类别 14X

Installation Method:

安装方式



Monolithic

同一方向安装

TractionBack®

Simplify your modular installation with Milliken's patented TractionBack®, an innovative backing system that is faster, more cost efficient, and environmentally superior to wet adhesives and peel-and-stick carpet tile.

www.millikencarpet.com



Declare.

总部地址: 上海市浦锦路2049号万科VMO国际商务广场37号楼220室

联系电话: 021-6403 9809 139 1860 5959 (微信同号)

公司网址: www.sheenone.com

分支机构: 南京、杭州、长沙、南昌、成都、广州、海口

